SHELVES

Depth adjustable shelves 1u fixed on four 19” mounting profiles

- Made of 1,2 mm sheet steel,
- 19” assembly, 1U height,
- Long supporting brackets included,
- Four mounting ears (two in front and two in back),
- Available depths : 250, 350, 450, 550, 650, 750 and 850 mm.

Load rating max. 80 kg balanced load; maximum load rating decreased to 25% when mounted on front extrusions only (250 and 350 mm shelf depth)
Color light grey (RAL7035).
Black color on request (RAL 9005).

part Number	wide	depth, mm	height, u	max mounting	weight, kg
1U-25-G-1.2-C	19”	250	1	414	2.2
1U-35-G-1.2-C	19”	350	1	514	3.0
1U-45-G-1.2-C	19”	450	1	614	3.8
1U-55-G-1.2-C	19”	550	1	714	4.6
1U-65-G-1.2-C	19”	650	1	814	5.3
1U-75-G-1.2-C	19”	750	1	914	6.1
1U-85-G-1.2-C	19”	850	1	1014	6.8

Shelves 2u fixed on two 19” mounting profiles

- Made of 1.5 mm sheet steel,
- 19” assembly, 2U height
- Two supporting ears on the front
- Available depths : 200, 300 mm
- Load rating max. 15 kg
- Colour light grey (RAL7035). Under order available black (RAL 9005).

part Number	wide	depth, mm	height, u	weight, kg
2U-20-B-1.5	19”	200	1	1.6
2U-30-B-1.5	19”	300	1	2.2

Sliding telescopic shelves 1u fixed on four 19” mounting profiles

- Made of 1.5 mm sheet steel,
- 19” assembly,
- Four mounting ears (two in front and two in back),
- Available for cabinet depths 600, 800
- Load rating max. 50 kg,
- Color light grey (RAL7035). Under order available black (RAL 9005).

part Number	wide	depth, mm	height, u	weight, kg
1U-45-B-Slide	19”	250	1	4.0
1U-55-B-Slide	19”	350	1	4.8