

# V-Lock C20 or C14 Male to V-Lock C19 or C13 Female 0,3 – 4.5Meters 16 Amp 250 Volt Hybrid Power Cord



1. REACH Statement
2. RoHs Compliant
3. WEEE Compliant
4. COC

Voltage	250 Volts
Amperage	16 Amps for C19-C20, and 10Amps for C13-C14
Male Plug	IEC60320 C20, C14
Plug Locking Type	V-Lock
Female Connector	IEC60320 C19, C13
Connector Locking	V-Lock
~ Length	0.3-4.5 meters
Gauge	1.50mm <sup>2</sup> /14 AWG for C19-C20 and 0,75mm <sup>2</sup> /18 AWG for C13-C14
Conductors	3 Wire
Conductor Color Code	Brown, Blue, and Green with Yellow Stripe   International Color Code (ICC)
~ Outside Diameter	9.25 - 9.45 for C19-C20 and mm 7.15 - 7.85 mm for C13-C14
Packaging	Loose and bundled.
Jacket	H05VV-F/SJT
Jacket Material	PVC
Jacket Temp. Rating	75° C
Color	Black
Testing	Each cord is tested for dielectric voltage-withstand (Hi-Pot), polarization and
Certifications	UL/cUL Listed, Sony Green Partner, Germany VDE, Australia SAA
Weight	0.3 kg