Termination Box TB-V24A

General Information

Multipurpose fiber optic distribution-termination box TB-V24A is used to provide a flexible platform to address the multitude of applications that exist in residential and commercial FTTx installations. Can be deliver with preinstalled SC adapters. Easy to install and is capable of being mounted directly to standard electrical junction boxes or directly to wall. The box interior can be configured to address slack storage, splicing, cross connect, hardened adapter applications or any combination.
The Distribution box kit includes all the necessary accessories –parts for complete box installation.

Application

•Outdoor use
•Designed for Wall mount applications
•Safety lock
•Available only for SC adapters (up to 24 Simplex SC adapters)
•Accepts loose tube, distribution cables
•Bend radius protection
•Rugged and durable construction for long term reliability (UV resistance)
•Resistance to vibration and shock
•Door with secure mechanism
•Design for small and medium volumes of fiber optic cables
•Whole front operation
•Convenient for expansion of capacity
•Reusable
•Sheath retention & central strength member termination system included
•ROHS compliance

Specification

Model	Capacity	Cable Port	PLC Splitter	Dimensions	Protection Class
TB-V24A	48 splices (4x12 splices)	2 inlet cable ports (for cables with max diameter 24.5mm)	1x8,1x16 PLC Splitter	272.5 x 235 x 84.5mm	IP 54