IDENTIFICATION CABLE TIES

The polyamide 6.6 cable ties with marking plate, allow a quick identification through specific marking on the plate.

Operating temperature: -40°C ÷ 85°C
Flammability rating: UL-94 V2.

IDENTIFICATION CABLE TIES

Code	Dimension (mm)	Plate height (mm)	Plate width (mm)	Ø Bundle max (mm)	Tensile strength (kg)	(N)	Bag pcs	Carton pcs
52100-ME	2,5x100	8	25,4	20	8,16	80	100	10.000
52200-ME	2,5x200	8	25,4	50	8,16	80	100	7.500

IDENTIFICATION CABLE TIES

Code	Dimension (mm)	Plate height (mm)	Plate width (mm)	Ø Bundle max (mm)	Tensile strength (kg)	(N)	Bag pcs	Carton pcs
52110-ME	2,5x110	9,1	20,4	20	8,16	80	100	10.000
52210-ME	2,5x210	9,1	20,4	52	8,16	80	100	7.500

IDENTIFICATION CABLE TIES

Code	Dimension (mm)	Plate height (mm)	Plate width (mm)	Ø Bundle max (mm)	Tensile strength (kg)	(N)	Bag pcs	Carton pcs
52190-ME	4,8x190	28	13	48	22,44	220	100	5.000
52270-ME	4,8x270	28	13	68	22,44	220	100	4.000