

Fiberglass FRP cable pullers

Cable pullers. Diameter 3.8-8 mm, length 15-200 m



Application

- Pulling cables and wires between telecommunication chambers
- Pushing cables under roads
- Installations in suspended ceilings
- Cleaning, clearing pipes, culverts, sewage
- Cable entry into the protective pipes

Structure

- FRP fiberglass
- High strength and elasticity cover with PE material (good sliding properties, protective function, yellow color)
- Powder coated blue frame
- The end of fiber ends with a guiding head
- Puller carrying handle



Part Number	Thickness [mm]	Length [m]	Size of reel [cm]	Weight [kg]
SRI-WS-03.015	3.8	15	35x15x55	2
SRI-WS-03.025	3.8	25	35x15x55	2.3
SRI-WS-03.050	3.8	50	35x15x55	2.7
SRI-WS-03.075	3.8	75	35x15x55	3
SRI-WS-03.100	3.8	100	35x15x55	3.3
SRI-WS-04.025	4.5	25	35x15x55	2.5
SRI-WS-04.050	4.5	50	35x15x55	2.9
SRI-WS-04.075	4.5	75	35x15x55	3.3
SRI-WS-04.100	4.5	100	35x15x55	3.6
SRI-WS-06.050	6	50	56x18x68	3.8
SRI-WS-06.075	6	75	56x18x68	4.6
SRI-WS-06.100	6	100	56x18x68	5.4
SRI-WS-06.150	6	150	56x18x68	7
SRI-WS-06.200	6	200	56x18x68	8.2
SRI-WS-08.050	8	50	70x20x85	13
SRI-WS-08.100	8	100	70x20x85	15

Thickness [mm]	Tensile strength [kN]	Crushing strength [kN]	Minimum bend radius [mm]
3.8	3.8	15	80
4.5	10	2	100
6	22	2.4	160
8	38	3	250

Accessories:

Ring terminals, repair sleeves



SRI-WS-LA; I-WS-GL

Cable stockings



SRI-WS-PJ; SRI-WS-PD; SRI-WS-PT

Flexible heads



SRI-EH