


10G SFP+ to RJ45 converter

10G media converter is an Ethernet converter between Ethernet electrical signal and optical signal. It converts between short distance twisted pair signal of 10GBase-TX and 10GBase-FX optical signal. Customer can choose different SFP modules to achieve the smooth conversion and connection. It has 1 10G fiber port and 1 RJ45 port. Except extending the transmission distance, there are also many other advantages such as isolation protection, good data security, working stability and easy maintenance.



Features

- Adopts Marvell chip, which ensures non-blocking data transmission, security and stability
- Supports 10Gbase—T to 10Gbase-SR/LR/ER/ZR on the Ethernet port
- Support 3R (Balanced amplification, clock extraction, integral regeneration) function on the fiber port to ensure small data jitter.
- Small latency on the data transmission.
- Support various wavelengths including 850nm, 1310nm, 1550nm and CWDM/DWDM under ITUT rule.
- Supports Jumbo Frame.
- 2-Year warranty
- Excellent heat elimination without cooling fan.




Technical specifications

Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/FX IEEE802.3ab 1000Base-T IEEE802.3z 10GBase-SX/LX	IEEE802.3x Flow control IEEE802.1q VLAN IEEE802.1p QoS IEEE802.1d Spanning Tree
Certifications	CCC, CE, FCC, RoHS	
Ethernet Port	<ul style="list-style-type: none"> ➤ Connector: RJ45 ➤ Data Rate: 10G ➤ Distance: 100m ➤ UTP Type: UTP-5E or higher level 	
Fiber Port	<ul style="list-style-type: none"> ➤ Connector: SFP slot ➤ Data Rate: 10Gbps ➤ Optical Wavelength: 850nm/1310nm/1490nm/1550nm ➤ Optical Fiber Type: Single mode 9/125μm; Multi mode 50/125μm、62.5/125μm ➤ Distance: 550m~100km 	
Performance	<ul style="list-style-type: none"> ➤ Processing Type: Store and Forward ➤ Transmission Mode: Full/half-duplex auto-adaptive ➤ MAC Table Size: 2K ➤ Buffer Space: 1Mbit ➤ Time Delay: <20μs 	
Power	<ul style="list-style-type: none"> ➤ Power type: external power supply ➤ Input Voltage: AC100V~240V 50/60Hz ➤ Connector: DC Socket ➤ Working Voltage: 5V4A&12V ➤ Power Consumption: 0.75W~3W 	
Environment	<ul style="list-style-type: none"> ➤ Storage Temperature: -40~70℃ ➤ Operating Temperature: -10~55℃ ➤ Relative Humidity: 5-90% (no condensation) 	
Warranty	1 year	
Physical Characteristics	<ul style="list-style-type: none"> ➤ Dimension: 117×85×21mm ➤ Weight: 0.1kg ➤ Color: Metal, Black 	



Dimensions



Ordering information

Part Number	Description
MCSFP10G/20G	10G SFP+ to RJ45 converter with 1 SFP+ port and 1 RJ45 port