

## TB-24SC Fiber optic distribution box IP65

TB-24SC optical distribution box is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.



### Features

- PC+ABS material used ensures the body strong and light..
- Wet-proof, water-proof, dust-proof, anti-aging
- Easy installations: Ready for wall mount - installation kits provided
- Space saving: Double-layer design for easier installation and maintenance
- Easy installations: Ready for wall mount - installation kits provided.
- Protection level up to IP65
- Cabinet can be installed by the way of wall-mounted or poled-mounted, suitable for both indoor and outdoor uses.
- Distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
- Cable, pigtails, patch cords are running through own path without disturbing each other, cassette type SC adapt or installation, easy maintenance.
- Lifetime 25 Years
- Operation Temperature -40C to +70C
- 5 years warranty

### Dimensions and Capability

Dimensions (W*H*D)	390mm*270mm*115mm
Adapter Capacity	SC 24; PLC 24
Number of Cable Entrance/Exit	4/2
Optional Accessories	Adapters, Pigtails
Weight	2.3KG
Number of Inputs	4 x 16 mm in Diameter 2 x 22 mm in Diameter
Max Diameter of Entry Cable	20 mm
Operation Conditions:	
Temperature	-40°C -- 60°C
Humidity	93% at 40°C
Air Pressure	62kPa - 101kPa
Protection degree	IP65

## Pictures

[www.sominetworks.com](http://www.sominetworks.com)



Part Number	Adapter Type	Dimensions
TB-24SC	24 x SC Simplex/LC duplex	390mm*270mm*115mm

