


Data sheet

Part No.	CL SW UV
Description	clip, interlinkable for fixation of rigid or pliable conduits on various surfaces, mounting possible with nails, screws or DSD plugs UV-stabilized
Colour	black, similar to RAL 9005
Fire Behaviour	non flame propagating

Standard: EN 61386-1, EN 61386-25



Working temperature
-25 to +60 °C

UV stabilized
true – up to 10 years

Art. No.	For tube diameter	PU	PU
082212	16 mm	100 pc	3200 pc
082179	20 mm	100 pc	2400 pc
082216	25 mm	100 pc	1600 pc
082220	32 mm	100 pc	1600 pc
082224	40 mm	50 pc	800 pc
082597	50 mm	50 pc	600 pc
082601	63 mm	25 pc	300 pc

Further technical details

Details	
Closed	False
Tackable	True
Max. number of tubes	1
Type of fastening	Screw hole
With inlay	False
Material	PVC-U

Cardboard packaging used is made from 100% waste paper and is fully recyclable, plastic packaging is fully recyclable.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, office@dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.