


Data sheet

Part No.	CL HG
Description	clip, interlinkable for fixation of rigid or pliable conduits on various surfaces, mounting possible with nails, screws or DSD plugs
Colour	light grey, similar to RAL 7035
Fire Behaviour	non flame propagating

Standard: EN 61386-1, EN 61386-25



Art. No.	For tube diameter	PU	PU
082211	16 mm	100 pc	3200 pc
082178	20 mm	100 pc	2400 pc
082215	25 mm	100 pc	1600 pc
082219	32 mm	100 pc	1600 pc
082223	40 mm	50 pc	800 pc
082596	50 mm	50 pc	600 pc
082600	63 mm	25 pc	300 pc

Further technical details

Details	
Closed	False
Tackable	True
Max. number of tubes	1
Type of fastening	Screw hole
With inlay	False
Material	PVC-U

Cardboard packaging used is made from 100% waste paper and is fully recyclable, plastic packaging is fully recyclable.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, office@dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.